

ROTOVAC® SHEARDRY

UPHOLSTERY TOOL INSTRUCTIONS

DO NOT USE OVER 200 DEGREES FAHRENHEIT (93 DEGREES CELSIUS) FOR CONTINUOUS CLEANING AS THIS MAY CAUSE THE PLASTIC TO DEFORM

1. Attach your solution hose to the male quick connect of the ShearDry at the end of the hide-a-hose.
2. Turn on the pump of your extractor. 75 to 150 psi is recommended
3. with the cleaning head of the ShearDry pointed into the recovery tank of a portable or into a sink, squeeze the solution trigger and adjust the water flow with the brass circular knob near the quick connect. Some of the water is vacuumed back into the two vacuum slots and some of the water will spray out.
4. Cover the flow control knob and the quick connect at the end of the hide-a-hose with the draw string bag to protect the floor and to act as a heat shield.
5. With the cleaning head on the fabric, squeeze the solution valve trigger. You can clean up, back, left, or right. As long as the cleaning head is on the fabric, there is no overspray or drippage. The ShearDry can clean in all directions.
6. If you keep the solution trigger on without the cleaning head on the fabric, some of the water will squirt out. So, let go of the solution valve trigger before removing the cleaning head from the fabric.
7. When cleaning a type of fabric that repels water and/or the flow is too high, water drips out the side of the head making the user think something is wrong. All that is needed to do is to turn down the flow control valve to put out less water.

Please see the videos at

<https://carpet-cleaning-equipment.net/sheardry.shtml>

<http://www.carpet-cleaning-equipment.net/all-videos.shtml>